

Draft Not Intended for Publication (03/20/04)

**G2000SS COMMERCIAL DIVING HELMET
POST DIVE CLEANING, INSPECTION & MAINTENANCE
CHECKLIST**

Note: This checklist is to be used with the G2000SS Helmet.

Note: This checklist should be completed at least once a day on any G2000SS Helmet.

Note: Parts of the Helmet, such as O-rings and other consumable components, may be reused so long as they are clean and do not show signs of damage and/or deterioration.

Note: G2000SS recommends that a certified G2000SS repair technician make all necessary repairs. If G2000SS owners choose to make their own repairs, it is strongly urged that the repairs are completed in accordance with the Helmet Manual. If any questions arise, the owners are urged to contact G2000SS for further guidance.

Date:	Helmet Serial Number:
Technician:	Print Name:

The G2000SS is a registered trademark of G2000SS, Inc. The use of this term and design for products not associated with G2000SS, Inc. is prohibited.

© Copyright 2004 G2000SS, Inc. All rights reserved. This manual and checklist is intended for the guidance of the user and owner of the G2000SS diving helmet. This manual and checklist may not be reproduced in any way without prior written permission of the G2000SS, Inc.

CHECKLIST

PROCEDURES	INITIALS
1. Lock and bleed down gas supply	_____
2. Disconnect Helmet Gas Connections and disconnect the communication wires. Replace hose caps onto the hose adaptor after sucking water out of the hose adaptor.	_____
3. Wash the outside of the Helmet completely with soap and water and rinse.	_____
4. Inspect the helmet in its entirety for damage.	_____
5. Remove the Helmet Liner and inspect for damage and/or deterioration. If Liner was exposed to water, clean and air dry Liner.	_____
6. Wash outside of the Demand Regulator with soap and water and rinse.	_____
7. If inside of regulator was exposed to salt or contaminated water, remove the oral nasal from the helmet and wash regulator with soap and water solution. If removal of regulator was necessary for better exposure, install regulator back into the helmet after cleaning. Note: Refer to Helmet Manual, Shell Final Assembly steps 20-23 in reverse and steps 4-6 in reverse, for guidance on installation and removal of the regulator.	_____
8. Remove the earphones.	_____

The G2000SS is a registered trademark of G2000SS, Inc. The use of this term and design for products not associated with G2000SS, Inc. is prohibited.

© Copyright 2004 G2000SS, Inc. All rights reserved. This manual and checklist is intended for the guidance of the user and owner of the G2000SS diving helmet. This manual and checklist may not be reproduced in any way without prior written permission of the G2000SS, Inc.

9. Remove microphone from the Oral Nasal Mask. Wash the Oral Nasal with a soap and water solution and rinse with fresh water.	<hr/>
10. Dry Helmet interior, including Oral Nasal Mask, by wiping. Wash with soap and water solution and rinse with fresh water.	<hr/>
11. Clean Neck Dam, Neck Retainer and Pull Pin Assemblies with soap and water solution. Rinse with fresh water.	<hr/>
12. Wipe helmet down to remove any standing water, and then let the rest air dry.	<hr/>
13. Wash the outside of all EGS components, Gas Cylinder, Submersible Pressure Gauge, and the Harness Assembly with soap and water solution. Rinse with fresh water.	<hr/>
14. Should any damage or deterioration be revealed during the inspection process, note below in “Comments” section.	<hr/>

Technician Signature: _____ Date: _____

Comments: _____

The G2000SS is a registered trademark of G2000SS, Inc. The use of this term and design for products not associated with G2000SS, Inc. is prohibited.

© Copyright 2004 G2000SS, Inc. All rights reserved. This manual and checklist is intended for the guidance of the user and owner of the G2000SS diving helmet. This manual and checklist may not be reproduced in any way without prior written permission of the G2000SS, Inc.